

# SAFETY DATA SHEET



Date issued : 04/16/2013  
 SDS number : TC-4207 PART A  
 Date revised : 01/09/2024  
 Revision number : 4

## TC-4207 PART A

### 1. Identification

**Product identifier:** TC-4207 PART A  
**Relevant identified uses:** Epoxy resin

**Manufacturer / Supplier**

BJB Enterprises, Inc.  
 14791 Franklin Avenue  
 Tustin, CA 92780  
**Emergency Phone:** (714) 734-8450

**Emergency telephone number (24 hour)**

**CHEMTREC (USA & Canada):** (800) 424-9300  
 or (703) 527-3887 CCN# 2820

### 2. Hazard identification

**Classification of the substance or mixture**

**Health hazards:**

Skin Irritation, Category 2  
 Eye Irritation, Category 2A  
 Skin Sensitization, Category 1

**Environmental hazards:**

Chronic Hazards to the Aquatic Environment, Category 2

**Label elements**



Exclamation  
 mark



Environment

**Signal word:** WARNING

**Hazard statement(s)**

H315: Causes skin irritation.  
 H319: Causes serious eye irritation.  
 H317: May cause an allergic skin reaction.  
 H411: Toxic to aquatic life with long lasting effects.

**Precautionary statement(s)**

**Prevention:**

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P264: Wash thoroughly after handling.  
 P272: Contaminated work clothing should not be allowed out of the workplace.  
 P280: Wear protective gloves/protective clothing/eye protection/face protection.  
 P273: Avoid release to the environment.

**Response:**

P302+P352: IF ON SKIN: Wash with plenty of soap and water.  
 P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
 P362+P364: Take off contaminated clothing and wash it before reuse.  
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337+P313: If eye irritation persists: Get medical advice/attention.

**TC-4207 PART A**

P391: Collect spillage.

**Disposal:**

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

**3. Composition/information on ingredients**

Chemical name	% w/w	CAS No.
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	60 - 80	25068-38-6
Calcium carbonate (limestone)	15 - 40	1317-65-3
Silicon dioxide	1 - 5	7631-86-9
Silica, Crystalline	< 0.1	14808-60-7

**4. First-aid measures**

**Eye:** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical advice/attention.

**Skin:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical advice/attention if irritation or rash develops. Wash clothing before reuse.

**Ingestion:** If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

**Inhalation:** Remove to fresh air. Seek medical advice/attention if breathing becomes difficult or if respiratory irritation develops.

**Indication of immediate medical attention and special treatment needed, if necessary:** Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

**5. Fire-fighting measures**

**Suitable extinguishing media:** Water spray, carbon dioxide, dry chemical, or foam.

**Hazardous combustion products:** Carbon monoxide and carbon dioxide.

**Fire fighting procedures:** Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

**Fire fighting equipment:** Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

**6. Accidental release measures**

**Small spill:** Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

**Large spill:** Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

**Environmental precautions**

**Water spill:** Do not discharge into drains, surface waters, or groundwater.

**General procedures:** Refer to section 8 of SDS for personal protection details.

**Release notes:** Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

**7. Handling and storage**

**General procedures:** Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

**Precautions for safe handling:** Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

**Conditions for safe storage:** Store in a dry and well-ventilated place, away from excessive heat, in original or similar container. Avoid

**TC-4207 PART A**

unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

**Storage temperature:** 65-80°F (18-27°C)

**Shelf life:** 12 months from date of shipment under manufacturers recommended storage conditions.

**8. Exposure controls/personal protection****Exposure controls**

Control parameters				
Chemical name	Occupational exposure limit values			
	Type		ppm	mg/m <sup>3</sup>
Calcium carbonate (limestone)	OSHA PEL	TWA	- <sup>[1]</sup>	15T 5R <sup>[1]</sup>
	NIOSH REL	TWA	- <sup>[1]</sup>	10T 5R <sup>[1]</sup>
Silicon dioxide	OSHA PEL	TWA	20 mppcf <sup>[2]</sup>	80 %SiO <sub>2</sub> <sup>[2]</sup>
	NIOSH REL	TWA	-	6
Silica, Crystalline	OSHA PEL	TWA	-	0.1
	ACGIH TLV	TWA	- <sup>[3]</sup>	0.025 <sup>[3]</sup>
	NIOSH REL	TWA	-	0.05

**Footnotes:**

1. T = Total dust, R = Respirable fraction
2. Mineral dusts
3. Respirable fraction

**Appropriate engineering controls:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

**Individual protection measures, such as personal protective equipment**

**Eye / face protection:** Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

**Skin protection - hand protection:** Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

**Respiratory protection:** Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

**Skin protection - other:** Protective clothing should be selected and used in accordance with "Guidelines for the Selection of Chemical Protective Clothing" published by ACGIH.

**Occupational hygiene practices:** Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

**Other use precautions:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

**9. Physical and chemical properties**

**Physical state:** Paste-Like

**Color:** Buff

**Odor:** Slight

**pH:** No data available

**Initial boiling point and boiling range:** No data available

**Flash point:** > 200°C (392°F) Pensky-Martens CC

**Vapor pressure:** No data available

**Relative vapor density:** No data available

**TC-4207 PART A****Relative density:** 1.4 (water=1) at 25°C (77°F)**Solubility:** Insoluble**Viscosity:** Paste-Like**10. Stability and reactivity****Reactivity:** Hazardous reactions will not occur under normal transport or storage conditions.**Chemical stability:** This product is stable under normal ambient conditions of temperature and pressure.**Conditions to avoid:** None Known**Possibility of hazardous reactions:** None Known**Hazardous decomposition products:** Carbon monoxide and carbon dioxide.**Incompatible materials:** Strong acids, strong bases, and strong oxidizing agents.**11. Toxicological information****Acute toxicity**

Chemical name	LD <sub>50</sub> (oral) mg/kg(rat)	LD <sub>50</sub> (dermal) mg/kg(rabbit)	LC <sub>50</sub> (inhalation) mg/l
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	> 2000 mg/kg Rat	> 2000 mg/kg Rat	No data available
Calcium carbonate (limestone)	No data available	No data available	No data available
Silicon dioxide	> 3300 mg/kg Rat	> 5000 mg/kg Rat	0.139 mg/l Rat (4 h)
Silica, Crystalline	No data available	No data available	No data available

**Skin corrosion / irritation:** Causes skin irritation.**Serious eye damage / irritation:** Causes serious eye irritation.**Respiratory or skin sensitization:** May cause sensitization by skin contact.**Germ cell mutagenicity:** No data available**Carcinogenicity**

Chemical name	NTP	IARC
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane		1
Silicon dioxide		3
Silica, Crystalline	1	1

**Reproductive toxicity:** No data available**Specific Target Organ Toxicity - single exposure:** No data available**Specific Target Organ Toxicity - repeated exposure:** No data available**Aspiration hazard:** No data available**12. Ecological information****Ecotoxicological information:** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Avoid release to the environment.**Persistence and degradability:** No data available**Bioaccumulative potential:** No data available**Environmental data:** This product may cause risk of hazardous effects to the environment.**Mobility in soil:** No data available**13. Disposal considerations**

**TC-4207 PART A**

**Disposal methods:** The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**14. Transport information****USA Department of Transport Regulations (DOT)**

**UN proper shipping name:** Environmentally hazardous substance, liquid, n.o.s. (**See Note**)

**Technical name:** Bisphenol A epoxy resin

**UN number:** UN3082

**Transport hazard class(es):** 9

**Packing group:** III

**NAERG:** 171

**Hazard label:** Class 9 (miscellaneous hazardous materials)

**Environmental hazards - marine pollutant:** Yes

**DOT other shipping information:** Only regulated for bulk and vessel shipments, per 49CFR171.4 (c) Exceptions. Except when all or part of the transportation is by vessel, the requirements of this subchapter specific to marine pollutants do not apply to non-bulk packagings transported by motor vehicle, rail car, or aircraft.

**ICAO / IATA - air**

**UN proper shipping name:** Environmentally hazardous substance, liquid, n.o.s. (**See Note**)

**Technical name:** Bisphenol A epoxy resin

**UN number:** UN3082

**Transport hazard class(es):** 9

**Packing group:** III

**ERG:** 9L

**Hazard label:** Class 9 (miscellaneous hazardous materials)

**Note:** Only regulated for bulk and vessel shipments, per 49CFR171.4 (c) Exceptions. Except when all or part of the transportation is by vessel, the requirements of this subchapter specific to marine pollutants do not apply to non-bulk packagings transported by motor vehicle, rail car, or aircraft.

**IMO / IMDG - sea**

**UN proper shipping name:** Environmentally hazardous substance, liquid, n.o.s.

**Technical name:** Bisphenol A epoxy resin

**UN number:** UN3082

**Transport hazard class(es):** 9

**Packing group:** III

**EmS:** F-A, S-F

**Environmental hazards - marine pollutant:** Yes

**Hazard label:** Class 9 (miscellaneous hazardous materials)

**15. Regulatory information****UNITED STATES****SARA Section 311/312 Hazard Categories**

**311/312 Health hazards:** Refer to Section 2 for hazard classification.

**313 reportable ingredients:** This product does not contain any substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

**CERCLA Hazardous Substances and Reportable Quantities (RQ)**

**CERCLA regulatory:** This product does not contain any substances regulated as a hazardous substance under the Comprehensive

**TC-4207 PART A**

Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

**TSCA (The Toxic Substances Control Act)**

**TSCA regulatory:** This product does not contain any substances subject to TSCA Section 12(b) export notification.

**TSCA Status:** This product or its components are listed in or exempt from the TSCA inventory requirements.

**Occupational safety and health administration (osha)**

**29 cfr1910.119---process safety management of highly hazardous chemicals:** None of the chemicals in this product are considered highly hazardous by OSHA.

**California Proposition 65:** This product does not contain any chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm.

**USA OSHA Hazard Communication Standard (29CFR 1910.1200):** The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

**CANADA**

**WHMIS Regulatory Status:** This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

**Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL):** All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

**16. Other information**


**Reason for issue:** Revision

**Date revised:** 01/09/2024

**Revision summary:** This SDS replaces the 07/20/2020 SDS.

**HMIS rating**

Health	<input type="checkbox"/>	<b>2</b>
Flammability	<input type="checkbox"/>	<b>1</b>
Physical hazard	<input type="checkbox"/>	<b>0</b>
Personal protection	<input checked="" type="checkbox"/>	<b>X</b>

**NFPA codes**

**HMIS ratings notes:** Personal Protection: See Section 8

**Manufacturer disclaimer:** This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.