

E236

Urethane Mold Release

Product Description

E236 is specially formulated as a silicone oil base release agent and anti-stick lubricant for molded urethanes and similar materials. It provides fast, easy part removal from molds and multiple part releases per application. Improves molding efficiency in many processes including pour cast urethanes, injection molding and extrusion molding.

Advantages:

- Silicone oils give the most amount of release, making demolding easier.
- Helps prevent silicone molds from drying out prematurely by acting as a mold conditioner.
- Improves parts appearance and reduces defects caused by sticking.
- Colorless and non-staining.
- A light coating produces the best results.
- Available in bulk as **Release #78**

Things to Note:

- Silicone oils can be transferred to the casting, making painting or bonding very difficult.
- Can leave a gloss finish on castings.
- Not recommended to be used for releasing silicone to silicone molds or parts.
- Not recommended for use with polyurethane foam systems.

Directions for Use

Shake well. Hold can 10 to 12 inches from mold surface. Apply a thin mist coating on the mold surface for best results.



Scan to watch our video,
Choosing Mold Release
for Cast Urethane & Silicone!

E236 Urethane Mold Release Technical Data

Active Ingredients	Proprietary urethane mold release
Flammability Rating	Non-flammable aerosol
Paintability	Not recommended when painting, decorating or gluing is required.