

SAFETY DATA SHEET



Date issued : 01/11/2023
SDS number : TC-812 REV 1 PART A

TC-812 REV 1 PART A

1. Identification

Product identifier: TC-812 REV 1 PART A
Relevant identified uses: Polyurethane resin

Manufacturer / Supplier

BJB Enterprises, Inc.
14791 Franklin Avenue
Tustin, CA 92780
Emergency Phone: (714) 734-8450

Emergency telephone number (24 hour)

CHEMTREC (USA & Canada): (800) 424-9300
or (703) 527-3887 CCN# 2820

2. Hazard identification**Classification of the substance or mixture****Health hazards:**

Acute Toxicity (Inhalation), Category 4
Skin Irritation, Category 2
Eye Irritation, Category 2A
Respiratory Sensitization, Category 1
Skin Irritation, Category 1B
Carcinogenicity, Category 2
Target Organ Toxicity (Single exposure), Category 3
Target Organ Toxicity (Repeated exposure), Category 2

Label elements

Health hazard

Exclamation
mark**Signal word:** DANGER**Hazard statement(s)**

H332: Harmful if inhaled.
H315: Causes skin irritation.
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317: May cause an allergic skin reaction.
H320: Causes eye irritation.
H351: Suspected of causing cancer.
H335: May cause respiratory irritation.
H373: May cause damage to organs through prolonged or repeated exposure.

Precautionary statement(s)**Prevention:**

P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P260: Do not breathe dust/fume/gas/mist/vapours/spray.
P264: Wash thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P272: Contaminated work clothing should not be allowed out of the workplace.

TC-812 REV 1 PART A

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P284: In case of inadequate ventilation wear respiratory protection.

Response:

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: IF exposed or concerned: Get medical advice/ attention.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.

P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician.

P362+P364: Take off contaminated clothing and wash it before reuse.

P370+P378: In case of fire: Use water spray, carbon dioxide, dry chemical, or foam for extinction.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

3. Composition/information on ingredients

Chemical name	% w/w	CAS No.
4,4'-Diphenylmethane diisocyanate	40 - 70	101-68-8
Modified MDI	10 - 30	Proprietary

4. First-aid measures

Eye: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical advice/attention.

Skin: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical advice/attention if irritation or rash develops. Wash clothing before reuse.

Ingestion: If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get immediate medical attention.

Indication of immediate medical attention and special treatment needed, if necessary: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. Fire-fighting measures

Suitable extinguishing media: Water spray, carbon dioxide, dry chemical, or foam.

Hazardous combustion products: Carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons, and hydrogen cyanide.

Fire fighting procedures: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

Fire fighting equipment: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

6. Accidental release measures

Small spill: Evacuate unnecessary personnel from the spill area. Wear necessary personal protective equipment (PPE) as specified in the SDS or the site emergency response plan. Eliminate all sources of ignition. Ensure adequate ventilation. Dike and contain spill. Prevent product from entering drains or waterways. Absorb with non-combustible material (such as sand, earth, diatomaceous earth, or vermiculite) and transfer to a container for disposal according to local/national regulations.

Environmental precautions

TC-812 REV 1 PART A

Water spill: Do not discharge into drains, surface waters, or groundwater.

General procedures: Refer to section 8 of SDS for personal protection details.

Release notes: Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

7. Handling and storage

General procedures: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

Precautions for safe handling: Avoid contact with eyes, skin, and clothing. Use only with adequate ventilation. Do not breathe vapors, mists, or dust. Use appropriate personal protective equipment (PPE) as specified in Section 8. Use in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

Conditions for safe storage: Store in a cool, dry place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials. Do not reseal container if moisture or water contamination is suspected. Water contaminated material in a sealed container may rupture due to pressure buildup.

Storage temperature: 65-80°F (18-27°C)

Shelf life: 6 months from date of shipment under manufacturers recommended storage conditions.

8. Exposure controls/personal protection**Exposure controls**

Control parameters				
Chemical name	Occupational exposure limit values			
	Type		ppm	mg/m ³
4,4'-Diphenylmethane diisocyanate	OSHA PEL	C	0.02	0.2
	ACGIH TLV	TWA	0.005	-
	NIOSH REL	TWA	0.005	0.05
		C	0.02 ^[1]	0.2 ^[1]
Footnotes:				
1. 10-minute				

Appropriate engineering controls: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Individual protection measures, such as personal protective equipment

Eye / face protection: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

Skin protection - hand protection: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

Respiratory protection: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Skin protection - other: Protective clothing should be selected and used in accordance with "Guidelines for the Selection of Chemical Protective Clothing" published by ACGIH.

Occupational hygiene practices: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

Other use precautions: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

9. Physical and chemical properties

Physical state: Liquid

Color: Yellow

TC-812 REV 1 PART A**Odor:** Slight aromatic**pH:** No data available**Freezing point:** No data available**Initial boiling point and boiling range:** No data available**Flash point:** > 200°C (392°F) Closed Cup**Vapor pressure:** No data available**Relative vapor density:** No data available**Relative density:** 1.22 (water=1) at 25°C (77°F)**Solubility:** Reacts slowly with water**Dynamic viscosity:** 50 Centipoise at 25°C (77°F)**10. Stability and reactivity****Reactivity:** Hazardous reactions will not occur under normal transport or storage conditions.**Chemical stability:** This product is stable under normal ambient conditions of temperature and pressure.**Conditions to avoid:** High temperatures, moisture, and freezing conditions.**Possibility of hazardous reactions:** Reaction with water produces carbon dioxide. Exothermic reaction with materials containing active hydrogen groups. The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of the reaction partners is good or is supported by stirring or by the presence of solvents. MDI is insoluble with, and heavier than water and sinks to the bottom but reacts slowly at the interface. A solid water-insoluble layer of polyurea is formed at the interface by liberating carbon dioxide gas.**Hazardous decomposition products:** Carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons, and hydrogen cyanide.**Incompatible materials:** Water, alcohols, amines, bases, and acids.**11. Toxicological information****Acute toxicity**

Chemical name	LD ₅₀ (oral) mg/kg(rat)	LD ₅₀ (dermal) mg/kg(rabbit)	LC ₅₀ (inhalation) mg/l
4,4'-Diphenylmethane diisocyanate	> 2000 mg/kg Rat	> 9400 mg/kg Rabbit	2.24 mg/l Rat (1 h, dust/mist)
Modified MDI	Not Established	Not Established	Not Established

Skin corrosion / irritation: Causes skin irritation.**Serious eye damage / irritation:** Causes serious eye irritation.**Respiratory or skin sensitization:** May cause sensitization by inhalation and skin contact.**Germ cell mutagenicity:** No data available**Carcinogenicity**

Chemical name	IARC
4,4'-Diphenylmethane diisocyanate	3

Specific Target Organ Toxicity - single exposure: May cause respiratory irritation.**Specific Target Organ Toxicity - repeated exposure:** Causes damage to organs through prolonged or repeated exposure.**Aspiration hazard:** No data available**12. Ecological information****Ecotoxicological information:** No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.**Persistence and degradability:** No data available**Bioaccumulative potential:** No data available**Other adverse effects:** This product may cause risk of hazardous effects to the environment.**Mobility in soil:** No data available

TC-812 REV 1 PART A**13. Disposal considerations**

Disposal methods: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty container: Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. **DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.**

14. Transport information

USA Department of Transport Regulations (DOT): Not Regulated

ICAO / IATA - air: Not Regulated

IMO / IMDG - sea: Not Regulated

15. Regulatory information**UNITED STATES****SARA Section 311/312 Hazard Categories**

311/312 Health hazards: Refer to Section 2 for hazard classification.

313 reportable ingredients: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

EPCRA Section 313 Toxic Chemicals

Chemical name	% w/w	CAS No.	Comments
4,4'-Diphenylmethane diisocyanate	40 - 70	101-68-8	Diisocyanate Compounds (Category Code N120)

CERCLA regulatory: This product contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

CERCLA Hazardous Substances and Reportable Quantities (RQ)

Chemical name	% w/w	CERCLA rq
4,4'-Diphenylmethane diisocyanate	40 - 70	5,000 lbs.

TSCA (The Toxic Substances Control Act)

TSCA regulatory: This product does not contain any substances subject to TSCA Section 12(b) export notification.

TSCA Status: This product or its components are listed in or exempt from the TSCA inventory requirements.

Occupational safety and health administration (osha)

29 cfr1910.119---process safety management of highly hazardous chemicals: None of the chemicals in this product are considered highly hazardous by OSHA.

California Proposition 65: This product does not contain any chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm.

USA OSHA Hazard Communication Standard (29CFR 1910.1200): The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

CANADA

WHMIS Regulatory Status: This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL): All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

16. Other information

TC-812 REV 1 PART A


Reason for issue: New Issue

Date Prepared: 01/11/2023

HMIS rating

Health	*	2
Flammability		2
Physical hazard		1
Personal protection	X	

NFPA codes



HMIS ratings notes: Personal Protection: See Section 8

Manufacturer disclaimer: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.