



SAFETY DATA SHEET

Date issued : 03/01/2013
 SDS number : TC-854 PART A
 Date revised : 07/07/2023
 Revision number : 4

TC-854 PART A

1. Identification

Product identifier: TC-854 PART A

Relevant identified uses: Polyurethane resin

Manufacturer / Supplier

BJB Enterprises, Inc.
 14791 Franklin Avenue
 Tustin, CA 92780
Emergency Phone: (714) 734-8450

Emergency telephone number (24 hour)

CHEMTREC (USA & Canada): (800) 424-9300
 or (703) 527-3887 CCN# 2820

2. Hazard identification

Classification of the substance or mixture

Health hazards:

Acute Toxicity (Inhalation), Category 4
 Skin Irritation, Category 2
 Eye Irritation, Category 2A
 Respiratory Sensitization, Category 1
 Skin Sensitization, Category 1
 Carcinogenicity, Category 2
 Target Organ Toxicity (Single exposure), Category 3
 Target Organ Toxicity (Repeated exposure), Category 2

Label elements



Health hazard



Exclamation
mark

Signal word: DANGER

Hazard statement(s)

H332: Harmful if inhaled.
 H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H317: May cause an allergic skin reaction.
 H351: Suspected of causing cancer.
 H335: May cause respiratory irritation.
 H373: May cause damage to organs through prolonged or repeated exposure.

Precautionary statement(s)

Prevention:

P201: Obtain special instructions before use.
 P202: Do not handle until all safety precautions have been read and understood.
 P260: Do not breathe dust/fume/gas/mist/vapours/spray.
 P271: Use only outdoors or in a well-ventilated area.
 P284: In case of inadequate ventilation wear respiratory protection.
 P264: Wash thoroughly after handling.

TC-854 PART A

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P308+P313: IF exposed or concerned: Get medical advice/attention.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

3. Composition/information on ingredients

Chemical name	% w/w	CAS No.
4,4'-Diphenylmethane diisocyanate	40 - 70	101-68-8
Oxirane, 2-methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatobenzene]	10 - 30	59675-67-1
Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer	7 - 13	25686-28-6
2,4'-Diphenylmethane diisocyanate	5 - 10	5873-54-1
1,3-butanediol, polymer with 1,1'-methylenebis[isocyanatobenzene], [(1-methyl-1,2-ethanediyl)bis(oxy)]bis[propanol] and 1,2-propanediol	1 - 5	150449-03-9
2,6-di-tert-butyl-p-cresol	0.1 - 1	128-37-0
Xylene	0.1 - 1	1330-20-7

4. First-aid measures

Eye: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical advice/attention.

Skin: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical advice/attention if irritation or rash develops. Wash clothing before reuse.

Ingestion: If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get immediate medical attention.

Indication of immediate medical attention and special treatment needed, if necessary: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. Fire-fighting measures

Suitable extinguishing media: Water spray, carbon dioxide, dry chemical, or foam.

Hazardous combustion products: Carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons, and hydrogen cyanide.

Fire fighting procedures: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

Fire fighting equipment: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

TC-854 PART A**6. Accidental release measures**

Small spill: Evacuate unnecessary personnel from the spill area. Wear necessary personal protective equipment (PPE) as specified in the SDS or the site emergency response plan. Eliminate all sources of ignition. Ensure adequate ventilation. Dike and contain spill. Prevent product from entering drains or waterways. Absorb with non-combustible material (such as sand, earth, diatomaceous earth, or vermiculite) and transfer to a container for disposal according to local/national regulations.

Environmental precautions

Water spill: Do not discharge into drains, surface waters, or groundwater.

General procedures: Refer to section 8 of SDS for personal protection details.

Release notes: Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

7. Handling and storage

General procedures: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

Precautions for safe handling: Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

Conditions for safe storage: Store in a dry and well-ventilated place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

Storage temperature: 65-80°F (18-27°C)

Shelf life: 6 months from date of shipment under manufacturers recommended storage conditions.

8. Exposure controls/personal protection**Exposure controls**

Control parameters				
Chemical name	Occupational exposure limit values			
	Type		ppm	mg/m ³
4,4'-Diphenylmethane diisocyanate	OSHA PEL	C	0.02	0.2
	ACGIH TLV	TWA	0.005	-
	NIOSH REL	TWA	0.005	0.05
		C	0.02 ^[1]	0.2 ^[1]
2,6-di-tert-butyl-p-cresol	NIOSH REL	TWA	-	10
Xylene	OSHA PEL	TWA	100	435
		STEL	-	-
	ACGIH TLV	TWA	100	-
		STEL	150	-
	NIOSH REL	TWA	100	435
		STEL	150	655

Footnotes:
1. 10-minute

Appropriate engineering controls: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Individual protection measures, such as personal protective equipment

Eye / face protection: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

Skin protection - hand protection: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer

TC-854 PART A

maximum protection.

Respiratory protection: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Skin protection - other: Protective clothing should be selected and used in accordance with "Guidelines for the Selection of Chemical Protective Clothing" published by ACGIH.

Occupational hygiene practices: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

Other use precautions: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

9. Physical and chemical properties

Physical state: Liquid

Color: Yellow

Odor: Slight

pH: No data available

Initial boiling point and boiling range: No data available

Flash point: > 101.7°C (215°F) Pensky-Martens CC

Vapor pressure: No data available

Relative vapor density: No data available

Relative density: 1.17 (water=1) at 25°C (77°F)

Solubility: Reacts with water

Dynamic viscosity: 165 Centipoise at 25°C (77°F)

VOC content: < 12.3 g/l Calculated. Theoretical VOC minus water and exempt solvents.

10. Stability and reactivity

Reactivity: Hazardous reactions will not occur under normal transport or storage conditions.

Chemical stability: This product is stable under normal ambient conditions of temperature and pressure.

Conditions to avoid: High temperatures, moisture, and freezing conditions.

Possibility of hazardous reactions: Reaction with water produces carbon dioxide. Exothermic reaction with materials containing active hydrogen groups. The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of the reaction partners is good or is supported by stirring or by the presence of solvents. MDI is insoluble with, and heavier than water and sinks to the bottom but reacts slowly at the interface. A solid water-insoluble layer of polyurea is formed at the interface by liberating carbon dioxide gas.

Hazardous decomposition products: Carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons, and hydrogen cyanide.

Incompatible materials: Water, alcohols, amines, bases, and acids.

11. Toxicological information

Acute toxicity

TC-854 PART A

Chemical name	LD ₅₀ (oral) mg/kg(rat)	LD ₅₀ (dermal) mg/kg(rabbit)	LC ₅₀ (inhalation) mg/l
4,4'-Diphenylmethane diisocyanate	> 2000 mg/kg Rat	> 9400 mg/kg Rabbit	2.24 mg/l Rat (1 h, dust/mist)
Oxirane, 2-methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1), polymer with 1,1'-methylenebis[4-isocyanatobenzene]	No data available	No data available	No data available
Benzene, 1,1'-methylenebis[4-isocyanato-, homopolymer	> 5000 mg/kg Rat	No data available	0.49 mg/l Rat
2,4'-Diphenylmethane diisocyanate	No data available	> 9400 mg/kg Rabbit	0.49 mg/l Rat (4 h)
1,3-butanediol, polymer with 1,1'-methylenebis[isocyanatobenzene], [(1-methyl-1,2-ethanediyl)bis(oxy)]bis[propanol] and 1,2-propanediol	No data available	No data available	No data available
2,6-di-tert-butyl-p-cresol	> 2900 mg/kg Rat	> 2000 mg/kg Rat	No data available
Xylene	3523 mg/kg Rat	12126 mg/kg Rabbit	5000 ppm Rat (4 h)

Skin corrosion / irritation: Causes skin irritation.

Serious eye damage / irritation: Causes serious eye irritation.

Respiratory or skin sensitization: May cause sensitization by inhalation and skin contact.

Germ cell mutagenicity: No data available

Carcinogenicity

Chemical name	IARC
4,4'-Diphenylmethane diisocyanate	3
2,6-di-tert-butyl-p-cresol	3
Xylene	3

Reproductive toxicity: No data available

Specific Target Organ Toxicity - single exposure: May cause respiratory irritation.

Specific Target Organ Toxicity - repeated exposure: May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard: No data available

12. Ecological information

Ecotoxicological information: No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.

Persistence and degradability: No data available

Bioaccumulative potential: No data available

Environmental data: No data available

Mobility in soil: No data available

13. Disposal considerations

Disposal methods: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

USA Department of Transport Regulations (DOT): Not Regulated

TC-854 PART A

ICAO / IATA - air: Not Regulated


IMO / IMDG - sea: Not Regulated

15. Regulatory information**UNITED STATES****SARA Section 311/312 Hazard Categories****311/312 Health hazards:** Refer to Section 2 for hazard classification.**313 reportable ingredients:** This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:**EPCRA Section 313 Toxic Chemicals**

Chemical name	% w/w	CAS No.	Comments
4,4'-Diphenylmethane diisocyanate	40 - 70	101-68-8	Diisocyanate Compounds (Category Code N120)

CERCLA regulatory: This product contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).**CERCLA Hazardous Substances and Reportable Quantities (RQ)**

Chemical name	% w/w	CERCLA rq
4,4'-Diphenylmethane diisocyanate	40 - 70	5,000 lbs.
Xylene	0.1 - 1	100 lbs.

TSCA (The Toxic Substances Control Act)**TSCA regulatory:** This product does not contain any substances subject to TSCA Section 12(b) export notification.**TSCA Status:** This product or its components are listed in or exempt from the TSCA inventory requirements.**Occupational safety and health administration (osha)****29 cfr1910.119--process safety management of highly hazardous chemicals:** None of the chemicals in this product are considered highly hazardous by OSHA.**California Proposition 65:**  **WARNING:** This product can expose you to chemicals including [see table below], which is [are] known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Chemical name	% w/w	Listed
Ethylbenzene	< 0.2	● Cancer
Cumene	< 0.01	● Cancer
Toluene	< 0.001	● Developmental Toxicity
Naphthalene	< 0.001	● Cancer
Benzene	< 0.0001	● Cancer ● Developmental Toxicity ● Male Reproductive
Ethyl acrylate	< 0.00001	● Cancer

USA OSHA Hazard Communication Standard (29CFR 1910.1200): The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.**CANADA****WHMIS Regulatory Status:** This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.**Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL):** All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).**16. Other information****Reason for issue:** Revision


TC-854 PART A

Date revised: 07/07/2023

Revision summary: This SDS replaces the 01/30/2020 SDS.

HMIS rating

Health	*	2
Flammability		1
Physical hazard		0
Personal protection	X	

NFPA codes**HMIS ratings notes:** Personal Protection: See Section 8**Manufacturer disclaimer:** This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.