

SAFETY DATA SHEET



Date issued : 08/20/2009
 SDS number : TC-896 PART A
 Date revised : 08/29/2023
 Revision number : 4

TC-896 PART A

1. Identification

Product identifier: TC-896 PART A

Relevant identified uses: Polyurethane resin

Manufacturer / Supplier

BJB Enterprises, Inc.
 14791 Franklin Avenue
 Tustin, CA 92780

Emergency Phone: (714) 734-8450

Emergency telephone number (24 hour)

CHEMTREC (USA & Canada): (800) 424-9300
 or (703) 527-3887 CCN# 2820

2. Hazard identification

Classification of the substance or mixture

Health hazards:

Acute Toxicity (Inhalation), Category 3
 Respiratory Sensitization, Category 1
 Skin Sensitization, Category 1

Label elements



Skull and
crossbones



Health hazard

Signal word: DANGER

Hazard statement(s)

H331: Toxic if inhaled.
 H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H317: May cause an allergic skin reaction.

Precautionary statement(s)

Prevention:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
 P271: Use only outdoors or in a well-ventilated area.
 P284: In case of inadequate ventilation wear respiratory protection.
 P272: Contaminated work clothing should not be allowed out of the workplace.
 P280: Wear protective gloves.

Response:

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P311: Call a POISON CENTER/doctor/physician.
 P302+P352: IF ON SKIN: Wash with plenty of soap and water.
 P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
 P362+P364: Take off contaminated clothing and wash it before reuse.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.
 P405: Store locked up.

Disposal:

TC-896 PART A

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

3. Composition/information on ingredients

| Chemical name | % w/w | CAS No. |
|--|---------|-------------|
| Hexane, 1,6-diisocyanato-, homopolymer | 60 - 80 | 28182-81-2 |
| Cycloaliphatic diisocyanate prepolymer | 10 - 30 | Proprietary |
| Dicyclohexylmethane-4,4'-diisocyanate | 1 - 5 | 5124-30-1 |
| Hexamethylene-1,6-diisocyanate | 0.1 - 1 | 822-06-0 |
| Isophorone diisocyanate | 0.1 - 1 | 4098-71-9 |

4. First-aid measures

Eye: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical advice/attention if irritation develops.

Skin: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical advice/attention if irritation or rash develops. Wash clothing before reuse.

Ingestion: If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get immediate medical attention.

Indication of immediate medical attention and special treatment needed, if necessary: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. Fire-fighting measures

Suitable extinguishing media: Water spray, carbon dioxide, dry chemical, or foam.

Hazardous combustion products: Carbon monoxide, carbon dioxide, and isocyanate-containing vapors.

Fire fighting procedures: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

Fire fighting equipment: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

6. Accidental release measures

Small spill: Evacuate unnecessary personnel from the spill area. Wear necessary personal protective equipment (PPE) as specified in the SDS or the site emergency response plan. Eliminate all sources of ignition. Ensure adequate ventilation. Dike and contain spill. Prevent product from entering drains or waterways. Absorb with non-combustible material (such as sand, earth, diatomaceous earth, or vermiculite) and transfer to a container for disposal according to local/national regulations.

Environmental precautions

Water spill: Do not discharge into drains, surface waters, or groundwater.

General procedures: Refer to section 8 of SDS for personal protection details.

Release notes: Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

7. Handling and storage

General procedures: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

Precautions for safe handling: Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

Conditions for safe storage: Store in a dry and well-ventilated place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

Storage temperature: 65-80°F (18-27°C)

Shelf life: 6 months from date of shipment under manufacturers recommended storage conditions.

TC-896 PART A

8. Exposure controls/personal protection

Exposure controls

| Control parameters | | | | | |
|---------------------------------------|--------------------------------|------------------------------------|---------------------|---------------------|---|
| | | Occupational exposure limit values | | | |
| Chemical name | Type | ppm | mg/m ³ | | |
| Dicyclohexylmethane-4,4'-diisocyanate | OSHA PEL | TWA | - | - | |
| | | STEL | - | - | |
| | | C | 0.01 ^[1] | 0.11 ^[1] | |
| | ACGIH TLV | TWA | 0.005 | - | - |
| | | STEL | - | - | - |
| | NIOSH REL | TWA | - | - | - |
| | | STEL | - | - | - |
| | | C | 0.01 | 0.11 | |
| | Hexamethylene-1,6-diisocyanate | OSHA PEL | TWA | - | - |
| STEL | | | - | - | |
| ACGIH TLV | | TWA | 0.005 | - | - |
| | | STEL | - | - | - |
| NIOSH REL | | TWA | 0.005 | 0.035 | |
| | | STEL | - | - | - |
| Isophorone diisocyanate | OSHA PEL | TWA | - | - | |
| | | STEL | - | - | |
| | ACGIH TLV | TWA | 0.005 | - | - |
| | | STEL | - | - | - |
| | NIOSH REL | TWA | 0.005 | 0.045 | |
| | | STEL | 0.02 ^[1] | 0.18 ^[1] | |
| Footnotes: | | | | | |
| 1. Skin | | | | | |

Appropriate engineering controls: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Individual protection measures, such as personal protective equipment

Eye / face protection: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

Skin protection - hand protection: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

Respiratory protection: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Skin protection - other: Protective clothing should be selected and used in accordance with "Guidelines for the Selection of Chemical Protective Clothing" published by ACGIH.

Occupational hygiene practices: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

Other use precautions: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is

TC-896 PART A

important. Follow all label precautions.

9. Physical and chemical properties

Physical state: Viscous liquid

Color: Pale yellow

Odor: Slight

pH: No data available

Initial boiling point and boiling range: No data available

Flash point: 157.2°C (315°F) Pinsky-Martens CC

Vapor pressure: No data available

Relative vapor density: No data available

Relative density: 1.13 (water=1) at 25°C (77°F)

Solubility: Reacts slowly with water

Dynamic viscosity: 2100 Centipoise at 25°C (77°F)

VOC content: < 0.1 g/l Calculated. Theoretical VOC minus water and exempt solvents.

10. Stability and reactivity

Reactivity: Hazardous reactions will not occur under normal transport or storage conditions.

Chemical stability: This product is stable under normal ambient conditions of temperature and pressure.

Conditions to avoid: High temperatures, moisture, and freezing conditions.

Possibility of hazardous reactions: Reacts violently with amines (exothermic). Exothermic reactions with acids, alkalis, powerful oxidants, and alcohols. Reacts with water, whereby carbon dioxide is produced; pressure may build up in closed containers (danger of bursting).

Hazardous decomposition products: Carbon monoxide, carbon dioxide, and isocyanate-containing vapors.

Incompatible materials: Water, alcohols, amines, acids, bases, and strong oxidizing agents.

11. Toxicological information**Acute toxicity**

| Chemical name | LD ₅₀ (oral) mg/kg(rat) | LD ₅₀ (dermal) mg/kg(rabbit) | LC ₅₀ (inhalation) mg/l |
|--|------------------------------------|---|------------------------------------|
| Hexane, 1,6-diisocyanato-, homopolymer | > 2500 mg/kg Rat | > 2000 mg/kg Rat | 4600 mg/m3 Rat |
| Cycloaliphatic diisocyanate prepolymer | No data available | No data available | No data available |
| Dicyclohexylmethane-4,4'-diisocyanate | 18200 mg/kg Rat | > 7000 mg/kg Rat | 0.33 mg/l Rat (4 h, dust/mist) |
| Hexamethylene-1,6-diisocyanate | 746 to 959 mg/kg Rat | > 7000 mg/kg Rat | 0.124 mg/l Rat (4 h, vapor) |
| Isophorone diisocyanate | 4814 mg/kg Rat | > 7000 mg/kg Rat | 0.031 mg/l Rat (4 h, dust/mist) |

Skin corrosion / irritation: No data available

Serious eye damage / irritation: No data available

Respiratory or skin sensitization: May cause sensitization by inhalation and skin contact.

Germ cell mutagenicity: No data available

Reproductive toxicity: No data available

Specific Target Organ Toxicity - single exposure: No data available

Specific Target Organ Toxicity - repeated exposure: No data available

Aspiration hazard: No data available

12. Ecological information

Ecotoxicological information: No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.

Persistence and degradability: No data available

Bioaccumulative potential: No data available

TC-896 PART A**Environmental data:** No data available**Mobility in soil:** No data available**13. Disposal considerations**


Disposal methods: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information**USA Department of Transport Regulations (DOT):** Not Regulated**ICAO / IATA - air:** Not Regulated**IMO / IMDG - sea:** Not Regulated**15. Regulatory information****UNITED STATES****SARA Section 311/312 Hazard Categories****311/312 Health hazards:** Refer to Section 2 for hazard classification.**313 reportable ingredients:** This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:**EPCRA Section 313 Toxic Chemicals**

| Chemical name | % w/w | CAS No. | Comments |
|---------------------------------------|-------|-----------|---|
| Dicyclohexylmethane-4,4'-diisocyanate | 1 - 5 | 5124-30-1 | Diisocyanate Compounds (Category Code N120) |

CERCLA regulatory: This product contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).**CERCLA Hazardous Substances and Reportable Quantities (RQ)**

| Chemical name | % w/w | CERCLA rq |
|--------------------------------|------------|-----------|
| Hexamethylene-1,6-diisocyanate | 0.1 - 1 | 100 lbs. |
| Naphthalene | < 0.0001 | 100 lbs. |
| Ethyl acrylate | < 0.000001 | 1,000 |

TSCA (The Toxic Substances Control Act)**TSCA regulatory:** This product does not contain any substances subject to TSCA Section 12(b) export notification.**TSCA Status:** This product or its components are listed in or exempt from the TSCA inventory requirements.**Occupational safety and health administration (osha)****29 cfr1910.119--process safety management of highly hazardous chemicals:** None of the chemicals in this product are considered highly hazardous by OSHA.**California Proposition 65:**  **WARNING:** This product can expose you to chemicals including [see table below], which is [are] known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

| Chemical name | % w/w | Listed |
|----------------|------------|----------|
| Naphthalene | < 0.0001 | ● Cancer |
| Ethyl acrylate | < 0.000001 | ● Cancer |

USA OSHA Hazard Communication Standard (29CFR 1910.1200): The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.**CANADA****WHMIS Regulatory Status:** This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

TC-896 PART A

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL): All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

16. Other information


Reason for issue: Revision

Date revised: 08/29/2023

Revision summary: This SDS replaces the 03/03/2020 SDS.

HMIS rating

| | | |
|----------------------------|----------|----------|
| Health | * | 2 |
| Flammability | | 1 |
| Physical hazard | | 1 |
| Personal protection | X | |

NFPA codes

HMIS ratings notes: Personal Protection: See Section 8

Manufacturer disclaimer: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.