



# SAFETY DATA SHEET

Date issued : 05/14/2021  
 SDS number : WC-55AM PART A  
 Date revised : 03/13/2025  
 Revision number : 1

## WC-55AM PART A

### 1. Identification

**Product identifier:** WC-55AM PART A

**Relevant identified uses:** Polyurethane resin

**Manufacturer / Supplier**

BJB Enterprises, Inc.  
 14791 Franklin Avenue  
 Tustin, CA 92780

**Emergency Phone:** (714) 734-8450

**Emergency telephone number (24 hour)**

**CHEMTREC (USA & Canada):** (800) 424-9300  
 or (703) 527-3887 CCN# 2820

### 2. Hazard identification

**Classification of the substance or mixture**

**Health hazards:**

Acute Toxicity (Inhalation), Category 3  
 Skin Irritation, Category 2  
 Eye Irritation, Category 2A  
 Respiratory Sensitization, Category 1  
 Skin Sensitization, Category 1  
 Target Organ Toxicity (Single exposure), Category 3

**Label elements**



Skull and  
crossbones



Health hazard

**Signal word:** DANGER

**Hazard statement(s)**

H331: Toxic if inhaled.  
 H315: Causes skin irritation.  
 H319: Causes serious eye irritation.  
 H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 H317: May cause an allergic skin reaction.  
 H335: May cause respiratory irritation.

**Precautionary statement(s)**

**Prevention:**

P260: Do not breathe dust/fume/gas/mist/vapours/spray.  
 P271: Use only outdoors or in a well-ventilated area.  
 P284: In case of inadequate ventilation wear respiratory protection.  
 P264: Wash thoroughly after handling.  
 P272: Contaminated work clothing should not be allowed out of the workplace.  
 P280: Wear protective gloves/protective clothing/eye protection/face protection.

**Response:**

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P310: Immediately call a POISON CENTER/doctor/physician.

**WC-55AM PART A**

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

**Storage:**

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

**Disposal:**

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

**3. Composition/information on ingredients**

Chemical name	% w/w	CAS No.
Cycloaliphatic diisocyanate prepolymer	40 - 80	Proprietary
Dicyclohexylmethane-4,4'-diisocyanate	15 - 20	5124-30-1
Hexamethylene-1,6-diisocyanate	< 0.1	822-06-0

**4. First-aid measures**

**Eye:** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical advice/attention.

**Skin:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical advice/attention if irritation or rash develops. Wash clothing before reuse.

**Ingestion:** If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

**Inhalation:** Remove to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get immediate medical attention.

**Indication of immediate medical attention and special treatment needed, if necessary:** Symptomatic and supportive therapy as needed.

Following severe exposure medical follow-up should be monitored for at least 48 hours.

**5. Fire-fighting measures**

**Suitable extinguishing media:** Water spray, carbon dioxide, dry chemical, or foam.

**Hazardous combustion products:** Carbon monoxide, carbon dioxide, nitrogen oxides, hydrogen cyanide, and isocyanate-containing vapor.

**Fire fighting procedures:** Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

**Fire fighting equipment:** Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

**6. Accidental release measures**

**Small spill:** Evacuate unnecessary personnel from the spill area. Wear necessary personal protective equipment (PPE) as specified in the SDS or the site emergency response plan. Eliminate all sources of ignition. Ensure adequate ventilation. Dike and contain spill. Prevent product from entering drains or waterways. Absorb with non-combustible material (such as sand, earth, diatomaceous earth, or vermiculite) and transfer to a container for disposal according to local/national regulations.

**Environmental precautions**

**Water spill:** Do not discharge into drains, surface waters, or groundwater.

**General procedures:** Refer to section 8 of SDS for personal protection details.

**Release notes:** Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

**7. Handling and storage**

**WC-55AM PART A**

**General procedures:** Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

**Precautions for safe handling:** Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

**Conditions for safe storage:** Store in a dry and well-ventilated place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

**Storage temperature:** 65-80°F (18-27°C)

**Shelf life:** 6 months from date of shipment under manufacturers recommended storage conditions.

<b>8. Exposure controls/personal protection</b>
---

**Exposure controls**

Control parameters				
Chemical name	Occupational exposure limit values			
	Type		ppm	mg/m <sup>3</sup>
Dicyclohexylmethane-4,4'-diisocyanate	OSHA PEL	TWA	-	-
		STEL	-	-
		C	0.01 <sup>[1]</sup>	0.11 <sup>[1]</sup>
	ACGIH TLV	TWA	0.005	-
		STEL	-	-
	NIOSH REL	TWA	-	-
		STEL	-	-
		C	0.01	0.11
	Hexamethylene-1,6-diisocyanate	OSHA PEL	TWA	-
STEL			-	-
ACGIH TLV		TWA	0.005	-
		STEL	-	-
NIOSH REL		TWA	0.005	0.035
		STEL	-	-
<b>Footnotes:</b>				
1. Skin				

**Appropriate engineering controls:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

**Individual protection measures, such as personal protective equipment**

**Eye / face protection:** Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

**Skin protection - hand protection:** Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

**Respiratory protection:** Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

**Skin protection - other:** Protective clothing should be selected and used in accordance with "Guidelines for the Selection of Chemical Protective Clothing" published by ACGIH.

**Occupational hygiene practices:** Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

**WC-55AM PART A**

**Other use precautions:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

**9. Physical and chemical properties**

**Physical state:** Liquid

**Color:** Colorless

**Odor:** Slight

**pH:** No data available

**Initial boiling point and boiling range:** No data available

**Flash point:** > 160°C (320°F) Pensky-Martens CC

**Vapor pressure:** No data available

**Relative vapor density:** No data available

**Relative density:** 1.09 (water=1) at 25°C (77°F)

**Solubility:** Reacts with water

**Dynamic viscosity:** 550 Centipoise at 25°C (77°F)

**VOC content:** Nil

**10. Stability and reactivity**

**Reactivity:** Hazardous reactions will not occur under normal transport or storage conditions.

**Chemical stability:** This product is stable under normal ambient conditions of temperature and pressure.

**Conditions to avoid:** High temperatures, moisture, and freezing conditions.

**Possibility of hazardous reactions:** Reacts violently with amines (exothermic). Exothermic reactions with acids, alkalis, powerful oxidants, and alcohols. Reacts with water, whereby carbon dioxide is produced; pressure may build up in closed containers (danger of bursting).

**Hazardous decomposition products:** Carbon monoxide, carbon dioxide, nitrogen oxides, hydrogen cyanide, and isocyanate-containing vapor.

**Incompatible materials:** Water, alcohols, amines, acids, bases, and strong oxidizing agents.

**11. Toxicological information****Acute toxicity**

Chemical name	LD <sub>50</sub> (oral) mg/kg(rat)	LD <sub>50</sub> (dermal) mg/kg(rabbit)	LC <sub>50</sub> (inhalation) mg/l
Cycloaliphatic diisocyanate prepolymer	No data available	No data available	No data available
Dicyclohexylmethane-4,4'-diisocyanate	18200 mg/kg Rat	> 7000 mg/kg Rat	0.33 mg/l Rat (4 h, dust/mist)
Hexamethylene-1,6-diisocyanate	746 to 959 mg/kg Rat	> 7000 mg/kg Rat	0.124 mg/l Rat (4 h, vapor)

**Skin corrosion / irritation:** Causes skin irritation.

**Serious eye damage / irritation:** Causes serious eye irritation.

**Respiratory or skin sensitization:** May cause sensitization by inhalation and skin contact.

**Germ cell mutagenicity:** No data available

**Reproductive toxicity:** No data available

**Specific Target Organ Toxicity - single exposure:** May cause respiratory irritation.

**Specific Target Organ Toxicity - repeated exposure:** No data available

**Aspiration hazard:** No data available

**12. Ecological information**

**Ecotoxicological information:** No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.

**Persistence and degradability:** No data available

**Bioaccumulative potential:** No data available

**WC-55AM PART A****Environmental data:** No data available**Mobility in soil:** No data available**13. Disposal considerations**

**Disposal methods:** The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**14. Transport information****USA Department of Transport Regulations (DOT):** Not Regulated**ICAO / IATA - air:** Not Regulated**IMO / IMDG - sea:** Not Regulated**15. Regulatory information****UNITED STATES****SARA Section 311/312 Hazard Categories****311/312 Health hazards:** Refer to Section 2 for hazard classification.**313 reportable ingredients:** This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:**EPCRA Section 313 Toxic Chemicals**

Chemical name	% w/w	CAS No.	Comments
Dicyclohexylmethane-4,4'-diisocyanate	15 - 20	5124-30-1	Diisocyanate Compounds (Category Code N120)

**CERCLA regulatory:** This product contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).**CERCLA Hazardous Substances and Reportable Quantities (RQ)**

Chemical name	% w/w	CERCLA rq
Hexamethylene-1,6-diisocyanate	< 0.1	100 lbs.

**TSCA (The Toxic Substances Control Act)****TSCA regulatory:** This product does not contain any substances subject to TSCA Section 12(b) export notification.**TSCA Status:** This product or its components are listed in or exempt from the TSCA inventory requirements.**Occupational safety and health administration (osha)****29 cfr1910.119--process safety management of highly hazardous chemicals:** None of the chemicals in this product are considered highly hazardous by OSHA.**California Proposition 65:** This product does not contain any chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm.**USA OSHA Hazard Communication Standard (29CFR 1910.1200):** The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.**CANADA****WHMIS Regulatory Status:** This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.**Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL):** All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).**16. Other information****Reason for issue:** Revision


**WC-55AM PART A**

Date revised: 03/13/2025

Revision summary: This SDS replaces the 05/20/2021 SDS.

**HMIS rating**

Health	*	3
Flammability		1
Physical hazard		1
Personal protection	X	

**NFPA codes****HMIS ratings notes:** Personal Protection: See Section 8**Manufacturer disclaimer:** This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.