

## SAFETY DATA SHEET



Date Issued : 06/21/2021  
SDS No : WC-85DL PART A

## WC-85DL PART A

## 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** WC-85DL PART A

**GENERAL USE:** Polyurethane resin

**MANUFACTURER**

BJB Enterprises, Inc.  
14791 Franklin Avenue  
Tustin, CA 92780  
**Emergency Phone:** (714) 734-8450

**24 HR. EMERGENCY TELEPHONE NUMBERS**

**CHEMTREC (USA & Canada):** (800) 424-9300  
or (703) 527-3887 CCN# 2820

## 2. HAZARDS IDENTIFICATION

**GHS CLASSIFICATIONS****Health:**

Acute Toxicity (Inhalation), Category 3  
Skin Irritation, Category 2  
Eye Irritation, Category 2A  
Respiratory Sensitization, Category 1  
Skin Sensitization, Category 1  
Target Organ Toxicity (Single exposure), Category 3

**GHS LABEL**

Skull and  
crossbones



Health hazard

**SIGNAL WORD:** DANGER

**HAZARD STATEMENTS**

H331: Toxic if inhaled.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H317: May cause an allergic skin reaction.  
H335: May cause respiratory irritation.

**PRECAUTIONARY STATEMENTS****Prevention:**

P260: Do not breathe dust/fume/gas/mist/vapours/spray.  
P271: Use only outdoors or in a well-ventilated area.  
P284: In case of inadequate ventilation wear respiratory protection.  
P264: Wash thoroughly after handling.  
P272: Contaminated work clothing should not be allowed out of the workplace.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.

**Response:**

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P310: Immediately call a POISON CENTER/doctor/physician.

**WC-85DL PART A**

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

**Storage:**

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

**Disposal:**

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

| Chemical Name                          | Wt.%     | CAS        |
|--|----------|------------|
| Hexane, 1,6-diisocyanato-, homopolymer | 60 - 100 | 28182-81-2 |
| Dicyclohexylmethane-4,4'-diisocyanate  | 15 - 20  | 5124-30-1  |
| Hexamethylene-1,6-diisocyanate         | < 0.1    | 822-06-0   |

**4. FIRST AID MEASURES**

**EYES:** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical advice/attention.

**SKIN:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical advice/attention if irritation or rash develops. Wash clothing before reuse.

**INGESTION:** If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

**INHALATION:** Remove to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get immediate medical attention.

**NOTES TO PHYSICIAN:** Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

**5. FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Water spray, carbon dioxide, dry chemical, or foam.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon monoxide, carbon dioxide, nitrogen oxides, hydrogen cyanide, and isocyanate-containing vapor.

**FIRE FIGHTING PROCEDURES:** Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

**FIRE FIGHTING EQUIPMENT:** Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

**6. ACCIDENTAL RELEASE MEASURES**

**SPILL AND LEAK PROCEDURES:** Evacuate unnecessary personnel from the spill area. Wear necessary personal protective equipment (PPE) as specified in the SDS or the site emergency response plan. Eliminate all sources of ignition. Ensure adequate ventilation. Dike and contain spill. Prevent product from entering drains or waterways. Absorb with non-combustible material (such as sand, earth, diatomaceous earth, or vermiculite) and transfer to a container for disposal according to local/national regulations.

**ENVIRONMENTAL PRECAUTIONS**

**WATER SPILL:** Do not discharge into drains, surface waters, or groundwater.

**GENERAL PROCEDURES:** Refer to section 8 of SDS for personal protection details.

**RELEASE NOTES:** Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

**WC-85DL PART A****7. HANDLING AND STORAGE**

**GENERAL PROCEDURES:** Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

**HANDLING:** Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

**STORAGE:** Store in a dry and well-ventilated place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

**STORAGE TEMPERATURE:** 65-80°F (18-27°C)

**SHELF LIFE:** 6 months from date of shipment under manufacturers recommended storage conditions.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****EXPOSURE GUIDELINES**

| OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200) |                                |                 |                     |                    |
|---|--------------------------------|-----------------|---------------------|--------------------|
| Chemical Name                               | Type                           | EXPOSURE LIMITS |                     |                    |
|   |                                | ppm             | mg/m <sup>3</sup>   |                    |
| Dicyclohexylmethane-4,4'-diisocyanate       | OSHA PEL                       | TWA             | -                   | -                  |
|   |                                | STEL            | -                   | -                  |
|   |                                | C               | 0.01 <sup>[1]</sup> | 011 <sup>[1]</sup> |
|   | ACGIH TLV                      | TWA             | 0.005               | -                  |
|   |                                | STEL            | -                   | -                  |
|   | NIOSH REL                      | TWA             | -                   | -                  |
|   |                                | STEL            | -                   | -                  |
|   |                                | C               | 0.01                | 0.11               |
|   | Hexamethylene-1,6-diisocyanate | OSHA PEL        | TWA                 | -                  |
| STEL  |                                |                 | -                   | -                  |
| ACGIH TLV                                   |                                | TWA             | 0.005               | -                  |
|   |                                | STEL            | -                   | -                  |
| NIOSH REL                                   |                                | TWA             | 0.005               | 0.035              |
|   |                                | STEL            | -                   | -                  |
| <b>Footnotes:</b>                           |                                |                 |                     |                    |
| 1. Skin                                     |                                |                 |                     |                    |

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

**PERSONAL PROTECTIVE EQUIPMENT**

**EYES AND FACE:** Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

**SKIN:** Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

**RESPIRATORY:** Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

**PROTECTIVE CLOTHING:** Protective clothing should be selected and used in accordance with "Guidelines for the Selection of Chemical Protective Clothing" published by ACGIH.

**WORK HYGIENIC PRACTICES:** Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

**WC-85DL PART A**

**OTHER USE PRECAUTIONS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**PHYSICAL STATE:** Liquid

**ODOR:** Slight

**COLOR:** Colorless

**pH:** No data available

**FLASH POINT AND METHOD:** > 160°C (320°F)

**VAPOR PRESSURE:** No data available

**VAPOR DENSITY:** No data available

**BOILING POINT:** No data available

**SOLUBILITY IN WATER:** Reacts with water

**SPECIFIC GRAVITY:** 1.09 (water=1) at 25°C (77°F)

**VISCOSITY #1:** 110 Centipoise at 25°C (77°F)

**(VOC):** Nil

**10. STABILITY AND REACTIVITY**

**REACTIVITY:** Hazardous reactions will not occur under normal transport or storage conditions.

**STABILITY:** This product is stable under normal ambient conditions of temperature and pressure.

**CONDITIONS TO AVOID:** High temperatures, moisture, and freezing conditions.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Reacts violently with amines (exothermic). Exothermic reactions with acids, alkalis, powerful oxidants, and alcohols. Reacts with water, whereby carbon dioxide is produced; pressure may build up in closed containers (danger of bursting).

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide, nitrogen oxides, hydrogen cyanide, and isocyanate-containing vapor.

**INCOMPATIBLE MATERIALS:** Water, alcohols, amines, acids, bases, and strong oxidizing agents.

**11. TOXICOLOGICAL INFORMATION****ACUTE TOXICITY**

| Chemical Name                          | ORAL LD <sub>50</sub> | DERMAL LD <sub>50</sub> | INHALATION LC <sub>50</sub>    |
|--|-----------------------|-------------------------|--------------------------------|
| Hexane, 1,6-diisocyanato-, homopolymer | > 2500 mg/kg Rat      | > 2000 mg/kg Rat        | 4600 mg/m <sup>3</sup> Rat     |
| Dicyclohexylmethane-4,4'-diisocyanate  | 18200 mg/kg Rat       | > 7000 mg/kg Rat        | 0.33 mg/l Rat (4 h, dust/mist) |
| Hexamethylene-1,6-diisocyanate         | 746 to 959 mg/kg Rat  | > 7000 mg/kg Rat        | 0.124 mg/l Rat (4 h, vapor)    |

**SKIN CORROSION/IRRITATION:** Causes skin irritation.

**SERIOUS EYE DAMAGE/IRRITATION:** Causes serious eye irritation.

**RESPIRATORY OR SKIN SENSITISATION:** May cause sensitization by inhalation and skin contact.

**GERM CELL MUTAGENICITY:** No data available

**REPRODUCTIVE TOXICITY:** No data available

**STOT-SINGLE EXPOSURE:** May cause respiratory irritation.

**STOT-REPEATED EXPOSURE:** No data available

**ASPIRATION HAZARD:** No data available

**12. ECOLOGICAL INFORMATION**

**ECOTOXICOLOGICAL INFORMATION:** No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.

**CHEMICAL FATE INFORMATION:** No data available

**WC-85DL PART A****BIOACCUMULATION/ACCUMULATION:** No data available**ENVIRONMENTAL DATA:** No data available**DISTRIBUTION:** No data available**13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**14. TRANSPORT INFORMATION****DOT (DEPARTMENT OF TRANSPORTATION):** Not Regulated**AIR (ICAO/IATA):** Not Regulated**VESSEL (IMO/IMDG):** Not Regulated**15. REGULATORY INFORMATION****UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)****311/312 HEALTH HAZARDS:** Refer to Section 2 for hazard classification.**313 REPORTABLE INGREDIENTS:** This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:**EPCRA SECTION 313 SUPPLIER NOTIFICATION**

| Chemical Name                         | Wt.%    | CAS       | Comments                                    |
|---------------------------------------|---------|-----------|---|
| Dicyclohexylmethane-4,4'-diisocyanate | 15 - 20 | 5124-30-1 | Diisocyanate Compounds (Category Code N120) |


**CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)****CERCLA REGULATORY:** This product contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

| Chemical Name                  | Wt.%  | CERCLA RQ |
|--------------------------------|-------|-----------|
| Hexamethylene-1,6-diisocyanate | < 0.1 | 100 lbs.  |

**TSCA (TOXIC SUBSTANCE CONTROL ACT)****TSCA REGULATORY:** This product does not contain any substances subject to TSCA Section 12(b) export notification.**TSCA STATUS:** This product or its components are listed in or exempt from the TSCA inventory requirements.**OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)****29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS:** None of the chemicals in this product are considered highly hazardous by OSHA.**CALIFORNIA PROPOSITION 65:** This product does not contain any chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm.**OSHA HAZARD COMM. RULE:** The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.**CANADA****WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):** This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.**DOMESTIC SUBSTANCE LIST (INVENTORY):** All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).**GENERAL COMMENTS:** No data available**16. OTHER INFORMATION**

**WC-85DL PART A****REASON FOR ISSUE:** New Issue**Date Prepared:** 06/21/2021**HMIS RATING**

|                            |   |          |
|----------------------------|---|----------|
| <b>HEALTH</b>              | * | <b>3</b> |
| <b>FLAMMABILITY</b>        |   | <b>1</b> |
| <b>PHYSICAL HAZARD</b>     |   | <b>1</b> |
| <b>PERSONAL PROTECTION</b> |   | <b>X</b> |

**NFPA CODES****HMIS RATINGS NOTES:** Personal Protection: See Section 8

**MANUFACTURER DISCLAIMER:** This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.