



SAFETY DATA SHEET

Date issued : 10/05/2020
 SDS number : CF-60AM PART A
 Date revised : 04/11/2024
 Revision number : 1

CF-60AM PART A

1. Identification

Product identifier: CF-60AM PART A
Relevant identified uses: Polyurethane resin

Manufacturer / Supplier

BJB Enterprises, Inc.
 14791 Franklin Avenue
 Tustin, CA 92780
Emergency Phone: (714) 734-8450

Emergency telephone number (24 hour)

CHEMTREC (USA & Canada): (800) 424-9300
 or (703) 527-3887 CCN# 2820

2. Hazard identification

Classification of the substance or mixture

Health hazards:

Acute Toxicity (Inhalation), Category 4
 Skin Irritation, Category 2
 Eye Irritation, Category 2A
 Respiratory Sensitization, Category 1
 Skin Sensitization, Category 1
 Carcinogenicity, Category 2
 Target Organ Toxicity (Single exposure), Category 3
 Target Organ Toxicity (Repeated exposure), Category 2

Label elements



Health hazard



Exclamation
mark

Signal word: DANGER

Hazard statement(s)

H332: Harmful if inhaled.
 H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H317: May cause an allergic skin reaction.
 H351: Suspected of causing cancer.
 H335: May cause respiratory irritation.
 H373: May cause damage to organs through prolonged or repeated exposure.

Precautionary statement(s)

Prevention:

P201: Obtain special instructions before use.
 P202: Do not handle until all safety precautions have been read and understood.
 P260: Do not breathe dust/fume/gas/mist/vapours/spray.
 P271: Use only outdoors or in a well-ventilated area.
 P284: In case of inadequate ventilation wear respiratory protection.
 P264: Wash thoroughly after handling.

CF-60AM PART A

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P308+P313: IF exposed or concerned: Get medical advice/ attention.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

3. Composition/information on ingredients

Chemical name	% w/w	CAS No.
4,4'-Diphenylmethane diisocyanate	30 - 50	101-68-8
Benzene, 1,1'-methylenebis[isocyanato-, homopolymer	10 - 15	39310-05-9
Benzene, 1,1'-methylenebis[isocyanato-	4 - 7	26447-40-5

4. First-aid measures

Eye: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical advice/attention.

Skin: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical advice/attention if irritation or rash develops. Wash clothing before reuse.

Ingestion: If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get immediate medical attention.

Indication of immediate medical attention and special treatment needed, if necessary: Symptomatic and supportive therapy as needed.

Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. Fire-fighting measures

Suitable extinguishing media: Water fog, dry chemical, foam, or carbon dioxide.

Hazardous combustion products: Carbon monoxide, carbon dioxide, nitrogen oxides, and hydrogen cyanide.

Fire fighting procedures: Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

Fire fighting equipment: Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

6. Accidental release measures

Small spill: Evacuate unnecessary personnel from the spill area. Wear necessary personal protective equipment (PPE) as specified in the SDS or the site emergency response plan. Eliminate all sources of ignition. Ensure adequate ventilation. Dike and contain spill. Prevent product from entering drains or waterways. Absorb with non-combustible material (such as sand, earth, diatomaceous earth, or vermiculite) and transfer to a container for disposal according to local/national regulations.

Environmental precautions

CF-60AM PART A

Water spill: Do not discharge into drains, surface waters, or groundwater.

General procedures: Refer to section 8 of SDS for personal protection details.

Release notes: Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

7. Handling and storage

General procedures: Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

Precautions for safe handling: Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

Conditions for safe storage: Store in a dry and well-ventilated place, away from excessive heat, in original or similar container. Avoid unnecessary contact. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials.

Storage temperature: 65-80°F (18-27°C)

Shelf life: 6 months from date of shipment under manufacturers recommended storage conditions.

8. Exposure controls/personal protection**Exposure controls**

Control parameters				
Chemical name	Occupational exposure limit values			
	Type		ppm	mg/m ³
4,4'-Diphenylmethane diisocyanate	OSHA PEL	C	0.02	0.2
	ACGIH TLV	TWA	0.005	-
	NIOSH REL	TWA	0.005	0.05
		C	0.02 ^[1]	0.2 ^[1]
Footnotes:				
1. 10-minute				

Appropriate engineering controls: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Individual protection measures, such as personal protective equipment

Eye / face protection: Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

Skin protection - hand protection: Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

Respiratory protection: Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Skin protection - other: Protective clothing should be selected and used in accordance with "Guidelines for the Selection of Chemical Protective Clothing" published by ACGIH.

Occupational hygiene practices: Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

Other use precautions: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

9. Physical and chemical properties

Physical state: Liquid

Color: Pale yellow

Odor: Slight

CF-60AM PART A**pH:** No data available**Initial boiling point and boiling range:** No data available**Flash point:** > 200°C (392°F) Pensky-Martens CC**Vapor pressure:** No data available**Relative vapor density:** No data available**Relative density:** 1.12 (water=1) at 25°C (77°F)**Solubility:** Reacts with water**Auto-ignition temperature:** > 470°C (878°F)**Dynamic viscosity:** 450 Centipoise at 25°C (77°F)**VOC content:** Nil**10. Stability and reactivity****Reactivity:** Hazardous reactions will not occur under normal transport or storage conditions.**Chemical stability:** This product is stable under normal ambient conditions of temperature and pressure.**Conditions to avoid:** High temperatures, moisture, and freezing conditions.**Possibility of hazardous reactions:** Reaction with water produces carbon dioxide. Exothermic reaction with materials containing active hydrogen groups. The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of the reaction partners is good or is supported by stirring or by the presence of solvents. MDI is insoluble with, and heavier than water and sinks to the bottom but reacts slowly at the interface. A solid water-insoluble layer of polyurea is formed at the interface by liberating carbon dioxide gas.**Hazardous decomposition products:** Carbon monoxide, carbon dioxide, nitrogen oxides, and hydrogen cyanide.**Incompatible materials:** Water, amines, acids, bases, and strong oxidizing agents.**11. Toxicological information****Acute toxicity**

Chemical name	LD ₅₀ (oral) mg/kg(rat)	LD ₅₀ (dermal) mg/kg(rabbit)	LC ₅₀ (inhalation) mg/l
4,4'-Diphenylmethane diisocyanate	> 2000 mg/kg Rat	> 9400 mg/kg Rabbit	2.24 mg/l Rat (1 h, dust/mist)
Benzene, 1,1'-methylenebis[isocyanato-, homopolymer	No data available	No data available	No data available
Benzene, 1,1'-methylenebis[isocyanato-	> 2000 mg/kg Rat	> 9400 mg/kg Rabbit	2.24 mg/l Rat (1 h, dust/mist)

Skin corrosion / irritation: Causes skin irritation.**Serious eye damage / irritation:** Causes serious eye irritation.**Respiratory or skin sensitization:** May cause sensitization by inhalation and skin contact.**Germ cell mutagenicity:** No data available**Carcinogenicity**

Chemical name	IARC
4,4'-Diphenylmethane diisocyanate	3

Reproductive toxicity: No data available**Specific Target Organ Toxicity - single exposure:** May cause respiratory irritation.**Specific Target Organ Toxicity - repeated exposure:** May cause damage to organs through prolonged or repeated exposure.**Aspiration hazard:** No data available**12. Ecological information****Ecotoxicological information:** No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.

CF-60AM PART A**Persistence and degradability:** No data available**Bioaccumulative potential:** No data available**Environmental data:** No data available**Mobility in soil:** No data available**13. Disposal considerations**

Disposal methods: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information**USA Department of Transport Regulations (DOT):** Not Regulated**ICAO / IATA - air:** Not Regulated**IMO / IMDG - sea:** Not Regulated**15. Regulatory information****UNITED STATES****SARA Section 311/312 Hazard Categories****311/312 Health hazards:** Refer to Section 2 for hazard classification.**313 reportable ingredients:** This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:**EPCRA Section 313 Toxic Chemicals**

Chemical name	% w/w	CAS No.	Comments
4,4'-Diphenylmethane diisocyanate	30 - 50	101-68-8	Diisocyanate Compounds (Category Code N120)

CERCLA regulatory: This product contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).**CERCLA Hazardous Substances and Reportable Quantities (RQ)**

Chemical name	% w/w	CERCLA rq
4,4'-Diphenylmethane diisocyanate	30 - 50	5,000 lbs.

TSCA (The Toxic Substances Control Act)**TSCA regulatory:** This product does not contain any substances subject to TSCA Section 12(b) export notification.**TSCA Status:** This product or its components are listed in or exempt from the TSCA inventory requirements.**Occupational safety and health administration (osha)****29 cfr1910.119--process safety management of highly hazardous chemicals:** None of the chemicals in this product are considered highly hazardous by OSHA.**California Proposition 65:** This product does not contain any chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm.**USA OSHA Hazard Communication Standard (29CFR 1910.1200):** The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.**CANADA****WHMIS Regulatory Status:** This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.**Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL):** All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

CF-60AM PART A**16. Other information**


Reason for issue: Revision

Date revised: 04/11/2024

Revision summary: This SDS replaces the 10/06/2020 SDS.

HMIS rating

Health	*	2
Flammability		1
Physical hazard		1
Personal protection	X	

NFPA codes

HMIS ratings notes: Personal Protection: See Section 8

Manufacturer disclaimer: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.